

# Rigid Vinyl Series – Wall Mounted Pathmarking Door Signs

The **Rigid Vinyl Series – Wall Mounted** Photoluminescent Pathmarking Signs provide visibility and indicate direction of egress in all light conditions. The signs are designed to be installed on the wall beside egress doors with a 3M Foam tape. The photoluminescent signs are visible for many hours after the lights go out, having been charged from sunlight or artificial light.



**UL 1994 AND  
ULC 572 Listed**

<b>EXIT TO THE RIGHT</b>	<b>EXIT TO THE LEFT</b>	<b>FINAL EXIT TO THE RIGHT</b>	<b>FINAL EXIT TO THE LEFT</b>	<b>EXIT THROUGH LOBBY LEFT</b>	<b>EXIT THROUGH LOBBY RIGHT</b>
<b>RAE2122-G250R</b>	<b>RBE2122-G250R</b>	<b>RAF2128-G250R</b>	<b>RBF2128-G250R</b>	<b>RBY4219-G250R</b>	<b>RAY4219-G250R</b>
8.4" x 8.89" (213.36mm x 226mm)	8.4" x 8.89" (213.36mm x 226mm)	8.4" x 11.1" (213.36mm x 282mm)	8.4" x 11.1" (213.36mm x 282mm)	16.4" x 7.4" (416.56mm x 188mm)	16.4" x 7.4" (416.56mm x 188mm)

**The Ecoglo Rigid Vinyl Series – Wall Mounted Pathmarking Door Signs meets the following Building, Accesible Design, Fire & Life Safety Codes:**

- IBC/IFC 2009, 2012 (Section 1024-Luminous Egress Path Markings) and 2015-2021 (Section 1025)
- ULC 590 S
- ULC 572 S
- CSA B651
- ISO/FDIS 2145

**Installation Instructions**

- Installs easily with 3M foam tape. Some surface preparation is required to ensure a strong bond.
- The foam tape allows for a strong installation on a variety of surfaces. The rigidity of the product spreads any applied load over a greater area of installation adhesion.

**Benefits and Technical Details:** Ecoglo Rigid Vinyl Series - Wall Mounted Pathmarking Door Signs meets or exceeds the performance criteria specified in the following tests or standards:

**Brightness**

High visibility in dark or light conditions.

- ASTM E2073-02, Standard Test Method for Photopic Luminance of Photoluminescent (Phosphorescent) Markings.
- ISO 17398:2004 Clause 7.11, Safety Colours and Safety Signs- Classification, Performance and Durability of Safety Signs
- UL 1994 Listed – IMZI.SA3353
- ULC 572 Listed – IMZI7.SA3353

**Washability**

Easy Cleaning.

- ASTM D4828-94(2003), Standard Test Methods for Practical Washability of Organic Coatings.

**Radioactivity**

No radioactivity or toxicity.

- Toxicity: Bombardier SMP 800-C (2000), Toxic Gas Generation Test.

**Flammability**

Does not burn.

- ASTM E162-02, Standard Test Method for Surface Flammability of Materials Using a Radiant Heat Energy Source.

Contact Ecoglo Inc. for a quick quote or to obtain more information about our emergency lighting products.

**KINESIK Engineered Products Incorporated**

2213 North Sheridan Way  
Mississauga, Ontario L5K 1A3  
Canada

Phone: 855.364.7763  
Fax: 800.769.4463  
[www.kinesik.ca](http://www.kinesik.ca)